

Rain Bird Synergy Automatic Controller



Features

- ❖ 16-station output
- ❖ Operates up to 2 valves per station plus a master valve
- ❖ Selectable input power: 110V AC, 220V AC, or 12V DC
- ❖ Backwash on time stamp, elapsed time or pressure differential
- ❖ Programmable filter-backwash frequency, duration and delay
- ❖ Manual start with station advance and stop
- ❖ Water and bug resistant enclosure
- ❖ Pre-dwell 0-5 minutes
- ❖ Alarms events displayed on digital screen display including output terminals for light and/or siren
 - Continuous backwash
 - Short circuit of solenoid
 - High pressure with automatic pump shutdown
 - Faulty panel
 - Faulty pressure differential switch
- ❖ 72-hour power backup in the event of a power outage
- ❖ Digital display with selection of English or Spanish
 - Real-time hours and minutes
 - Number of backwash events
 - Number of backwash events within a time period
- ❖ Wire loom block for quick and easy solenoid wire installation and removal
- ❖ USB port for historical data logging
- ❖ Made in the USA

Rain Bird Corporation

6991 E. Southpoint Road
Tucson, AZ 85756
Phone: (520) 741-6100
Fax: (520) 741-6522

Rain Bird Technical Services

(800) RAINBIRD (1-800-724-6247)
(U.S. and Canada)

Rain Bird Corporation

970 West Sierra Madre Avenue
Azusa, CA 91702
Phone: (626) 812-3400
Fax: (626) 812-3411

Specification Hotline

800-458-3005 (U.S. and Canada)

Rain Bird International, Inc.

1000 West Sierra Madre Ave.
Azusa, CA 91702
Phone: (626) 963-9311
Fax: (626) 852-7343

The Intelligent Use of Water™
www.rainbird.com
industrial.rainbird.com